

EPS[®] 2533

Suggested Formulation

EPS[®] 2533 is a styrenated acrylic emulsion offering exceptional ink and tannin blocking characteristics, as well as excellent adhesion and early water resistance. EPS[®] 2533 provides paint formulators a waterborne alternative to solvent-based primers and is ideal for use as a universal primer or low gloss topcoat on ferrous and non-ferrous metal, cementitious, wood and plastic substrates.

PROPERTIES

- Exceptional alkali resistance, ideal for use on "hot" cementitious substrates
- Exceptional tannin stain block
- Exceptional water-based and solvent-based ink marker stain block
- Exceptional exterior durability
- Excellent corrosion resistance even without the use of anticorrosive pigments or additives
- Excellent early water resistance
- Excellent adhesion to ferrous and non-ferrous metal substrates, glossy alkyds and chalky substrates
- Made without APEO surfactants

Specifications

Weight Solids	45.5 +/- 0.7%
Weight/Gallon	8.60 +/- 0.10
pH	7.0 - 8.0

Typical Properties

Volume Solids	43.7 +/- 0.7%
MFFT	9° C
Volatile(s)	Water

Suggested Coalescing Solvent(s)

(% Solvent on Binder Solids – Pass 40°F LTC Test)

Texanol / EPS 9147 or Blends	5 - 6%
------------------------------	--------

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com

2/5/2021

TECHNICAL SUPPORT: These guidelines are offered to assist the paint formulator in achieving the high performance properties noted and are offered for illustration purposes only; the paint formulator bears sole responsibility for the performance of the final coating product.

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epsc.ca.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epsc.ca/galleries/pdfs/salesterms.pdf>.

Suggested Formulation

Formula: EPS 2533 WHT1 (186-1, 3/3/09) Universal Stain-Blocking Primer – White

<u>Pounds</u>	<u>Gallons</u>	<u>Raw Material</u>	<u>Supplier</u>	<u>Instructions</u>
66.6	8.00	Water		Add with good agitation
15.0	1.69	Tamol 2001	Dow	
2.0	0.28	Surfynol 104A	Evonik	
1.0	0.13	Drewplus L-475	Troy	
4.0	0.51	AMP 95	Angus	
150.0	4.38	Ti-Pure R902	Chemours	
100.0	4.43	Cal White	Imerys	
15.0	0.32	Zoco 103	Zochem	Grind to 6 NS
619.2	72.00	EPS 2533	EPS	Letdown
2.0	0.26	Drewplus L-475	Troy	Add with good agitation
1.5	0.16	Nuosept 498	Troy	
14.1	1.61	EPS 9147	EPS	
35.0	3.75	Ethylene Glycol		
10.0	1.20	Sodium Nitrite (4%)		
4.2	0.50	Water		
<u>8.0</u>	<u>0.81</u>	Optiflo L100	BYK	
1047.6	100.15	Totals		

Formulation Parameters

Weight Solids	54.7 %
Volume Solids	43.5 %
Weight / Gallon	10.46 # / gal
Pigment Volume Conc:	22.49 %
Pigment / Binder	0.94 : 1
VOC	100 g / L
	0.83 # / gal

Typical Paint Properties

Viscosity (Stormer)	90 – 100 KU
pH	9.0- 10.0
Color	White

Suggested Application Methods

Brush, Roller, Airless Spray

Questions? Call EPS Customer Service @ 1-800-654-4242 / Email: info@eps-materials.com

2/5/2021

TECHNICAL SUPPORT: These guidelines are offered to assist the paint formulator in achieving the high performance properties noted and are offered for illustration purposes only; the paint formulator bears sole responsibility for the performance of the final coating product.

SDS: For details on health, safety and handling information, Safety Data Sheets (SDS) are available at www.epscsa.com.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. EPS assumes no obligation or liability for use of this information. UNLESS EPS AGREES OTHERWISE IN WRITING, EPS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR FREEDOM FROM PATENT INFRINGEMENT. EPS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. Unless otherwise agreed in writing, all sales of EPS products are governed by the EPS Terms and Conditions of Sale, available at <https://www.epscsa.com/galleries/pdfs/salesterms.pdf>.